

# Skid Steer / Forklift



Made in Thailand

**OFF-THE-ROAD TYRES-BIAS**





OFF-THE-ROAD TYRES-BIAS  
**Skid Steer**

EL76

EL78

EL79



- A Company Established in Year 1958
- No. 1 Tyre Manufacturer in China
- No. 9 of Top 75 Global Tyre Manufacturers in Year 2021
- Sale Revenue reached \$3.896 Billion in Year 2020



# OFF-THE-ROAD TYRES-BIAS

## Skid Steer



### EL76

Premium deep block skid steer tyre

Size	Ply Rating	Standard Rim	Tread Depth		Overall Diameter		Section Width		Max. Load Capacity		Cold Inflation Pressure	
			(mm)	(32nds)	(mm)	(inch)	(mm)	(inch)	(kg)	(lbs)	(kPa)	(psi)
10-16.5	12	8.25	25	31	773	30.43	264	10.39	2375	5240	620	90
12-16.5	14	9.75	35	44	831	32.72	307	12.09	3075	6785	620	90



### EL78

Economic lug skid steer tyre

Size	Ply Rating	Standard Rim	Tread Depth		Overall Diameter		Section Width		Max. Load Capacity		Cold Inflation Pressure	
			(mm)	(32nds)	(mm)	(inch)	(mm)	(inch)	(kg)	(lbs)	(kPa)	(psi)
10-16.5	10	8.25	22.5	28	773	30.43	264	10.39	2135	4711	520	75
12-16.5	12	9.75	23	29	831	32.72	307	12.09	2865	6322	550	80



### EL79

Premium lug skid steer tyre

Size	Ply Rating	Standard Rim	Tread Depth		Overall Diameter		Section Width		Max. Load Capacity		Cold Inflation Pressure	
			(mm)	(32nds)	(mm)	(inch)	(mm)	(inch)	(kg)	(lbs)	(kPa)	(psi)
10-16.5	10	8.25	22	28	773	30.43	264	10.39	2135	4711	520	75
12-16.5	12	9.75	24	30	831	32.72	307	12.09	2865	6322	550	80

EDT

CL626

CL622

CL621

OFF-THE-ROAD TYRES-BIAS  
**Forklift**



## OFF-THE-ROAD TYRES-BIAS

# Forklift



## CL621

Standard pneumatic tyre

Size	Ply Rating	Standard Rim	Tread Depth		Overall Diameter		Section Width		Max. Load Capacity		Cold Inflation Pressure	
			(mm)	(32nds)	(mm)	(inch)	(mm)	(inch)	(kg)	(lbs)	(kPa)	(psi)
5.00-8	10	350D	11.0	14	470	18.50	137	5.39	1150	2537	1000	145
6.00-9	10	4.00E	12.5	16	540	21.26	160	6.30	1505	3321	860	125
7.00-9	10	5.00S	10.0	13	590	23.23	190	7.48	1995	4402	860	125
6.50-10	10	5.00F	12.0	15	590	23.23	175	6.89	1655	3652	790	115
7.00-12	12	5.00S	13.0	16	676	26.61	190	7.48	2375	5240	860	125
8.25-12	12	6.5	19.0	24	765	30.12	235	9.25	3060	6752	720	104
6.00-15	10+	4.50E	14.0	18	705	27.76	170	6.69	2185	4821	830	120
8.25-15	14	6.5	16.0	20	840	33.07	235	9.25	3775	8330	830	120
9.00-16	14	6.50H	16.0	20	890	35.04	255	10.04	4495	9918	760	110
8.25-20	14	6.5	15.0	19	974	38.35	235	9.25	3865	8528	830	120
9.00-20	16	7.0	17.0	21	1018	40.08	259	10.20	4715	10404	860	125
18x7-8	14	4.33R	16.0	20	173	6.81	465	18.31	1440	3177	900	131
23x9-10	18	6.50F	14.0	18	595	23.43	225	8.86	3160	6973	1050	152
27x10-12	14	8.00G	14.0	18	690	27.17	255	10.04	3210	7083	720	104
28x9-15	14	7.0	16.0	20	710	27.95	220	8.66	3050	6730	970	141
250-15	16	7.5	21.0	26	735	28.94	250	9.84	3865	8528	930	135
300-15	18+	8.0	23.0	29	840	33.07	300	11.81	5530	12202	830	120
21x8-9	14	6.00E	16.0	20	510	20.08	198	7.80	2040	4501	1000	145
7.00-15	12	5.5	15.0	30	750	29.53	200	7.87	2420	5340	860	125
7.50-15	12	6.0	16.0	30	780	30.71	215	8.46	2600	5737	790	115



## CL622

Standard pneumatic tyre

Size	Ply Rating	Standard Rim	Tread Depth		Overall Diameter		Section Width		Max. Load Capacity		Cold Inflation Pressure	
			(mm)	(32nds)	(mm)	(inch)	(mm)	(inch)	(kg)	(lbs)	(kPa)	(psi)
10.00-20	16	7.5	22.0	28	1073	42.24	278	10.94	-	-	800	116
12.00-20	16	8.5	25.0	31	1145	45.08	315	12.40	-	-	700	102
	18	8.5	25.0	31	1145	45.08	315	12.40	-	-	700	102

# OFF-THE-ROAD TYRES-BIAS

# Forklift



## CL626

Premium pneumatic tyre

Size	Ply Rating	Standard Rim	Tread Depth		Overall Diameter		Section Width		Max. Load Capacity		Cold Inflation Pressure	
			(mm)	(32nds)	(mm)	(inch)	(mm)	(inch)	(kg)	(lbs)	(kPa)	(psi)
10.00-20	18	7.5	26.5	33	1099	43.27	278	10.94	6755	14905	910	132
12.00-20	20	8.5	26.5	33	1173	46.18	315	12.40	8055	17773	880	128



## EDT

Premium pneumatic tyre

Size	Ply Rating	Standard Rim	Tread Depth		Overall Diameter		Section Width		Max. Load Capacity		Cold Inflation Pressure	
			(mm)	(32nds)	(mm)	(inch)	(mm)	(inch)	(kg)	(lbs)	(kPa)	(psi)
5.00-8	10	3.50D	17.5	22	470	18.50	137	5.39	1150	2537	1000	145
6.00-9	12	4.00E	19.3	24	540	21.26	160	6.30	1675	3696	1030	149
6.50-10	12	5.00F	23.8	30	590	23.23	175	6.89	1860	4104	790	115
7.00-12	14	5.00S	22.0	28	676	26.61	190	7.48	2590	5715	1000	145
7.00-15	14	5.5	23.0	29	750	29.53	200	7.87	3140	6928	1000	145
7.50-15	14	6.0	21.5	27	780	30.71	215	8.46	3375	7447	925	134
8.25-15	14	6.5	24.5	31	840	33.07	235	9.25	3775	8330	830	120
28×9-15	14	7.0	20.6	26	710	27.95	220	8.66	3050	6730	970	141
28×12-15	24	9.75BD	16.0	21	711	27.99	305	12.01	2360	5207	960	139



[www.zc-rubber.com](http://www.zc-rubber.com)



zc rubber



zc rubber



ZHONGCE RUBBER GROUP CO., LTD.

