



NI-PON®

TYRE CATALOGUE



- A Company Established in Year 1958
- No. 1 Tyre Manufacturer in China
- No. 9 of Top 75 Global Tyre Manufacturers in Year 2023
- Sale Revenue Reached USD4.2 Billion in Year 2022

NI-PON® CONTENTS



Long Haul

03 - 13



Regional

14 - 21



Mixed Service

22 - 33



- Super value tyre for long haul application
- Stone ejector platforms prevent tread damage from stone drilling
- Four main straight grooves guarantee excellent drainage ability and even wear resulting in long tread life



AT167

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11.00R20	J/18	152/149K	15.0	8.0	1085	293	3550	7825	930	135	3250	7165	930	135
265/70R19.5	H/16	140/138M	13.0	7.50	867	262	2500	5510	775	112	2360	5200	775	112
265/70R19.5	J/18	143/141J	13.0	7.50	867	262	2725	6005	850	123	2575	5675	850	123
11R22.5	H/16	148/145M	14.2	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	14.5	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
255/70R22.5	H/16	140/137M	14.0	7.50	930	255	2500	5510	830	120	2300	5070	830	120
275/70R22.5	H/16	148/145M	14.0	8.25	958	276	3150	6940	900	130	2900	6395	900	130
295/75R22.5	G/14	144/141L	14.2	9.00	1020	298	2800	6175	760	110	2575	5675	760	110
295/80R22.5	J/18	152/149M	14.0	9.00	1050	298	3550	7830	900	131	3250	7610	900	131
315/80R22.5	J/18	154/151M(156/153L)	14.5	9.00	1076	312	3750	8270	830	120	3450	7610	830	120
11R24.5	H/16	149/146L	14.2	8.25	1104	279	3250	7160	830	120	3000	6610	830	120

- High cost performance tyres suitable for long haul application
- Four straight ditch designs ensure drainage performance
- High saturation pattern design enhances tyre mileage



AT196

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
295/80R22.5	J/18	152/149M	13.5	9.00	1050	298	3550	7830	900	131	3250	7610	900	131
315/80R22.5	L/20	157/154K	13.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130



- High cost performance tyres suitable for long haul application
- The new formula design enhances tyre mileage and reduces tyre heat generation
- Finite element simulation analysis, More uniform distribution of tyre contact pressure, improve uneven wear performance



AT186

● : Recommendable
● : Available



- Super value tyre for long haul application
- Wide base multi-rib trailer tyres with durable compound
- Improved tread design promises outstanding stability with optimized footprint and better tyre life



AT131

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure								Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)								(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
295/80R22.5	J/18	152/149M	13.5	9.00	1050	298	3550	7830	900	131	3250	7610	900	131	385/65R22.5	L/20	160K(158L)	15.5	11.75	1072	389	4500	9920	900	130	-	-	-	-
315/80R22.5	L/20	157/154K	13.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130															

- Super value tyre suitable for steer and trailer axle
- Multi kerf provides outstanding traction on wet and snow road surface
- Four grooves with zigzag designed provide excellent groove crack prevention



● : Recommendable
● : Available

AZ170

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
385/55R22.5	L/20	160K(158L)	13.0	12.25	996	386	4500	9920	900	130	-	-	-	-
385/65R22.5	L/20	160K	13.5	11.75	1072	389	4500	9920	900	130	-	-	-	-

- Super value tyre for long haul application
- Improved tread compound and tyre casing provide super balance between cost and performance



● : Recommendable
● : Available

AT161

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	H/16	148/145M	15.5	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	15.5	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
295/80R22.5	J/18	152/149M	15.0	9.00	1044	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5	J/18	154/151M(156/153L)	15.0	9.00	1076	312	3750	8270	830	120	3450	7610	830	120
315/80R22.5	L/20	157/154K	15.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130

- Super value tyre for long haul application
- Straight simple rib pattern improves even wearing and efficient water evacuation for excellent wet traction and handling
- Cross rib sipes slice through water for solid control on wet roads



● : Recommendable
● : Available

AT160

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	H/16	148/145M	14.2	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
11R24.5	H/16	149/146L	14.2	8.25	1104	279	3250	7160	830	120	3000	6610	830	120

- Super value tyre for long haul application
- Optimized block design prevents retaining objects for improved damage resistance
- Strong casing resists cuts and punctures for enhanced toughness and long casing life



● : Recommendable
● : Available

AD178

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	H/16	148/145L	20.6	8.25	1065	279	3150	6940	850	123	2900	6390	850	123
295/75R22.5	G/14	144/141L	20.6	9.00	1020	298	2800	6175	760	110	2575	5675	760	110
11R24.5	H/16	149/146L	20.6	8.25	1116	279	3250	7160	830	120	3000	6610	830	120



Long Haul



Long Haul



- High cost performance tyres suitable for long haul application
- Classic block pattern, Better driving performance and grip performance
- Wider tread to increase tyre mileage



AD122

- : Recommendable
- : Available



- High cost performance tyres suitable for long haul application
- Classic block pattern, Better driving performance and grip performance
- Special tread compound and tyre casing offers good tyre mileage



AD150

- : Recommendable
- : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure								Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)								(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
295/80R22.5	J/18	152/149M	18.0	9.00	1050	298	3550	7830	900	131	3250	7160	900	131	315/80R22.5	J/18	154/151M(156/153L)	17.5	9.00	1082	312	3750	8270	830	120	3450	7610	830	120



Long Haul

- Super value tyre for long haul application
- Special tread compound and tyre casing offers good tyre mileage
- Computer designed tread guarantees good traction for highway service in all season conditions



● : Recommendable
● : Available

AD153

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
275/80R22.5	H/16	149/146L	17.0	8.25	1012	276	3250	7165	850	123	3000	6610	850	123
295/80R22.5	J/18	152/149L	19.0	9.00	1050	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5	J/18	154/151M(156/153L)	19.0	9.00	1082	312	3750	8270	830	120	3450	7610	830	120



Regional

- Super value tyre for regional application
- Wide base all routes trailer tyres with durable compound
- Good damage protection and even wear profile feature outstanding performance in all conditions



● : Recommendable
● : Available

AT132

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
385/65R22.5	L/20	160K(158L)	15.5	11.75	1072	389	4500	9920	900	130	-	-	-	-

- Super value tyre for regional application
- Five ribs ensure excellent comfort and outstanding traction on wet and dry surfaces
- Zig-zag pattern allows better tension distribution in tread grooves for even wear



•

: Recommendable

•

: Available

AZ128

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	H/16	148/145L	15.0	8.25	1054	279	3150	6940	850	123	2900	6390	850	123

- Super value tyre for regional application
- Four ribs design provides excellent footprint and more contact on the road surface
- Special tyre casing and compound offer great value by longer mileage with less cost



•

: Recommendable

•

: Available

AZ171

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	H/16	148/145L	15.5	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	16.0	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
295/80R22.5	J/18	152/149M	16.0	9.00	1044	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5	J/18	154/151M(156/153L)	16.0	9.00	1076	312	3750	8270	830	120	3450	7610	830	120
315/80R22.5	L/20	157/154K	16.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130



NEW

- High cost performance tyres suitable for regional application
- V-shaped stepped pattern groove design, prevention of stone inclusion and stone removal, Prevent groove cracking
- Latest comprehensive road condition tyre tread formula, Balancing tear resistance and heat generation, Better mileage for comprehensive road conditions



AZ189

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	H/16	146/143M	12.5	8.25	1054	279	3000	6610	830	120	2725	6005	830	120
12R22.5	J/18	152/149L	13.0	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
315/80R22.5	L/20	157/154K	13.5	9.00	1076	312	4125	9090	900	130	3750	8270	900	130



- Super value tyre for regional application
- Non-directional tread design for easy operating
- Open lug design helps provide traction in wet or snowy conditions



CM187/MZ187

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
9.00R20	H/16	144/142K	14.5	7.0	1019	259	2800	6175	900	130	2650	5840	900	130
11.00R20	J/18	152/149K	16.0	8.0	1085	293	3550	7825	930	135	3250	7165	930	135
12R22.5	J/18	152/149L	18.0	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
11R22.5(MZ187)	J/18	149/146L	20.6	8.25	1065	279	3250	7160	930	135	3000	6610	930	135



- Super value tyre for regional application
- Aggressive tread blocks with special tread compound provide good traction on paved roads for price-oriented customers
- Special tread design promises remarkable footprint and even wear to extend tread life



AD156

•

: Recommendable

•

: Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	H/16	148/145L	20.6	8.25	1065	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	19.0	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
295/80R22.5	J/18	152/149M	19.0	9.00	1050	298	3550	7830	900	131	3250	7160	900	131
11R24.5	H/16	149/146L	20.6	8.25	1116	279	3250	7160	830	120	3000	6610	830	120



- Super value tyre for regional application
- Special tread compounding ensuring longer wear life and service life
- Wide shoulder design helps even wear and longer mileage



AZ102

•

: Recommendable

•

: Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
12.00R24	L/20	160/157K	14.0	8.5	1226	315	4500	9920	900	131	4125	9090	900	131



- Super value tyre for regional application
- Four ribs ensure even wear and comfortable riding
- Siped zig-zag rib helps improve traction on wet and muddy surface



AZ166

•

: Recommendable

•

: Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
12.00R24	L/20	160/157K	15.0	8.5	1226	315	4500	9920	900	131	4125	9090	900	131



- Super value tyre for regional&mixed service application
- Variable groove angle for long mileage
- Stone ejector in the groove protect belt from stone drilling
- Zig-zag groove help improve traction on wet and muddy surface



AZ183

•

: Recommendable

•

: Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
10.00R20	J/18	149/146J	15.5	7.5	1054	278	3250	7160	930	135	3000	6610	930	135
11.00R20	J/18	152/149K	16.0	8.0	1085	293	3550	7825	930	135	3250	7165	930	135
12.00R20	J/18	154/151K	16.5	8.5	1125	315	3750	8270	830	120	3450	7610	830	120
11R22.5	H/16	148/145L	15.0	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	15.0	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
13R22.5	J/18	156/151K	15.0	9.75	1124	320	4000	8820	875	128	3450	7610	875	128
295/80R22.5	J/18	152/149L	15.0	9.00	1044	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5	J/18	154/151M(156/153L)	15.0	9.00	1076	312	3750	8270	830	120	3450	7610	830	120
11R24.5	H/16	149/146L	15.0	8.25	1104	279	3250	7160	830	120	3000	6610	830	120



Mixed Service



- High cost performance tyres suitable for regional application
- Wider and deeper tread to increase tyre mileage
- Crisscrossing patterned steel sheets, Excellent grip and slippery performance



AZ137

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
315/80R22.5	J/18	154/151M(156/153L)	16.5	9.00	1076	312	3750	8270	830	120	3450	7610	830	120



Mixed Service



- Super value tyre for regional&mixed service application
- Wide, deep tread helps provide long tread life in regional conditions
- Zig-zag ribs ensure even wear and grip on wet, dry and snowy roads



AZ188

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	H/16	148/145M	15.5	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	16.0	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
315/80R22.5	J/18	154/151M(156/153L)	15.5	9.00	1076	312	3750	8270	830	120	3450	7610	830	120
315/80R22.5	L/20	157/154K	15.5	9.00	1076	312	4125	9090	900	130	3750	8270	900	130



Mixed Service



- High cost performance tyres suitable for regional&mixed service application
- V-shaped stepped pattern groove design, prevention of stone inclusion and stone removal, Prevent groove cracking
- tyre shoulder horizontal pattern design, Improve heat dissipation performance, better grip and handling performance



AZ118

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
315/80R22.5	L/20	157/154K	14.5	9.00	1076	312	4125	9090	900	130	3750	8270	900	130
11R22.5	H/16	148/145L	13.0	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	14.5	9.00	1085	300	3550	7830	930	135	3250	7160	930	135



Mixed Service



- Super value tyre for regional&mixed service application
- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



AZ026

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
10.00R20	J/18	149/146J	16.0	7.5	1054	278	3250	7160	930	135	3000	6610	930	135
11.00R20	J/18	152/149K	16.0	8.0	1085	293	3550	7825	930	135	3250	7165	930	135
12.00R20	J/18	154/151K	17.5	8.5	1125	315	3750	8270	830	120	3450	7610	830	120



Mixed Service



- Super value tyre for regional&mixed service application
- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



AZ126

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
315/80R22.5	J/18	154/151M(156/150L)	15.5	9.00	1076	312	3750	8270	830	120	3450	7610	830	120
315/80R22.5	L/20	157/154K	15.5	9.00	1076	312	4125	9090	900	130	3750	8270	900	130



Mixed Service



- Super value tyre for regional&mixed service application
- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



AZ126T

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	H/16	148/145M	16.8	8.25	1054	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149L	16.0	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
295/80R22.5	J/18	152/149L	16.0	9.00	1044	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5	J/18	154/151M(156/150L)	16.0	9.00	1076	312	3750	8270	830	120	3450	7610	830	120
315/80R22.5	L/20	157/154K	16.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130
11R24.5	H/16	149/146L	16.8	8.25	1104	279	3250	7160	830	120	3000	6610	830	120



Mixed Service



- Super value tyre for regional&mixed service application
- 3 circumferential grooves ensures good directional stability, even wear and smooth ride
- Heavy siping provides good braking stability and high lateral traction on wet and dry surface
- Improved tread compound helps resist tears and ensure good mileage in on and off road use
- Sidewall reinforcing ribs protects against impacts and scuffing



CR926T

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
12.00R24	L/20	160/157K	16.0	8.5	1226	315	4500	9920	900	131	4125	9090	900	131



Mixed Service



- Super value tyre for mixed service application
- Drive axle tyre applicable for mud and sand terrain with short on high-way use
- Wide tread and open shoulder blocks help enhance traction and braking on rough roads with mud or gravel
- Special tread compounds resist chipping, chunking and tearing



EZ033

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
9.00R20	H/16	144/142K	17.0	7.0	1019	259	2800	6175	900	130	2650	5840	900	130
12.00R24	L/20	160/157K	16.0	8.5	1226	315	4500	9920	900	131	4125	9090	900	131
315/80R22.5	L/20	157/154K	16.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130



Mixed Service



- Super value tyre for mixed service application
- Aggressive blocks provides outstanding traction on rough roads
- Open shoulder tread design help promote self-cleaning ability



MD101

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
13R22.5	J/18	156/151K	19.0	9.75	1136	320	4000	8820	875	128	3450	7610	875	128
315/80R22.5	L/20	157/154K	19.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130



Mixed Service



- Super value tyre for mixed service application
- Aggressive lug design with larger blocks at tread center provides excellent traction
- Open shoulder tread design improves self-cleaning capacity for ease of maintenance



EZ175/EZ175A

● : Recommendable
● : Available

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single		Dual					
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
10.00R20	J/18	149/146D	20.0	7.5	1065	278	3250	7160	930	135	3000	6610	930	135
11.00R20	J/18	152/149D	20.0	8.0	1096	293	3550	7825	930	135	3250	7165	930	135
12.00R20	J/18	154/151F	21.0	8.5	1125	315	3750	8270	830	120	3450	7610	830	120
11R22.5	H/16	148/145J	19.5	8.25	1065	279	3150	6940	850	123	2900	6390	850	123
12R22.5	J/18	152/149F	19.5	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
295/80R22.5	J/18	152/149J	20.0	9.00	1050	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5(EZ175A)	L/20	157/154K	16.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130



NEW

- High cost performance tyres suitable for mixed service application
- The consistent and sturdy pattern design at the center of the tread, Reduce tyre tread damage and improve tyre life
- The tread adopts a wear-resistant and cutting resistant formula, Improve the comprehensive performance of tyres



● : Recommendable
● : Available

EZ177

Size	LR / PR	Service index	Tread Depth (mm)	Standard Rim	Overall Diameter (mm)	Section Width (mm)	Max. Load Capacity at Cold Inflation Pressure							
							Single				Dual			
							(kg)	(lbs)	(kPa)	(psi)	(kg)	(lbs)	(kPa)	(psi)
11R22.5	J/18	149/146K	19.5	8.25	1065	279	3250	7160	930	135	3000	6610	930	135
12R22.5	J/18	152/149K	19.5	9.00	1085	300	3550	7830	930	135	3250	7160	930	135
295/80R22.5	J/18	152/149J	19.5	9.00	1050	298	3550	7830	900	131	3250	7160	900	131
315/80R22.5	L/20	157/154K	20.0	9.00	1076	312	4125	9090	900	130	3750	8270	900	130

NOTES:




ZC-Rubber America Inc.

ZC-Rubber Mexican
(under construction)


ZC-Rubber Brasil Co. Ltd.


ZC-Rubber Europe Technical Center
ZC-Rubber Europe GmbH


ZC-Rubber Thailand Co. Ltd.


ZC-Rubber Indonesia
(under construction)



ZC-Rubber HQ
ZC-Rubber Tianjin
ZC-Rubber Chaoyang
ZC-Rubber Jiande
ZC-Rubber Qingquan
ZC-Rubber Yonggu
ZC-Rubber Anji
ZC-Rubber Jintan
ZC-Rubber Recycling
Tech. Co. Ltd.
Hangzhou ZC-Rubber
Auto Space Co. Ltd.



ZHONGCE RUBBER GROUP CO., LTD.